

Electrical

Antenna Size		1.8 M (71 in)
Operating Frequency	<i>Receive</i>	3.625 – 4.200 and 3.400 – 4.200 GHz
	<i>Transmit</i>	5.850 – 6.425 and 5.925 – 6.725 GHz
Midband Gain (± 0.2 dB)	<i>Receive</i>	35 dBi
	<i>Transmit</i>	39 dBi
Feed Type		Linear
3 dB Beamwidth	<i>Receive</i>	1.9°
	<i>Transmit</i>	1.3°
Antenna Noise Temperature		
10° elevation		56° K
20° elevation		49° K
30° elevation		47° K
Cross-Pol Isolation (Linear)		> 30dB (on axis)
Side Lobe Envelope, Co-Pol Tx (dB)		
100 λ /D $\theta \leq 20^\circ$		29-25 Log θ dBi
20° < $\theta \leq 26.3^\circ$		-3.5 dBi
26.3 < $\theta \leq 48^\circ$		32-25 Log θ dBi
$\theta > 48^\circ$		-10 dBi (average)
VSWR		1.3:1 Max.
Feed Interface	<i>Receive</i>	CPR 229 F
	<i>Transmit</i>	CPR 137 or Type N

Mechanical

Reflector Material		Glass Fiber Reinforced Polyester
Antenna Optics		Prime Focus, One Piece Offset Feed
Polarization Travel		$\pm 90^\circ$ Continuous
Mount Type		Elevation over Azimuth
Elevation Adjustment Range		5° to 90°, Continuous Fine Adjustment
Azimuth Adjustment Range		360°, Continuous, Fine Adjustment
Mast Pipe Size and Height		5" (126mm) dia, 48" (1220 mm) height
Shipping Weight		

Environmental Performance

Wind Loading	<i>Operational</i>	50 mph with 0.2° pointing error (80kmph)
	<i>Survival</i>	125 mph (201 km/h)
Temperature	<i>Operational</i>	-40° to 140° F (-40° to 60° C)
	<i>Survival</i>	-50° to 160° F (-46° to 71° C)
Rain	<i>Operational</i>	½ "/hr (1.27 cm/hr)
	<i>Survival</i>	2" /hr (5.08 cm/hr)
Ice	<i>Operational</i>	-----
	<i>Survival</i>	½ " (1.27 cm) radial



AGHAZCOM

P.O. Box 1796, 117 Gulshan-e-Iqbal
Pir Wadhi Road, Rawalpindi, Pakistan

Phone (92-51) 5473625

Fax (92-51) 5462087:

Email aghaz@comsats.net.pk